

532724

27 APR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/532724



(43) International Publication Date
13 May 2004 (13.05.2004)


PCT

(10) International Publication Number
WO 2004/040038 A1

- (51) International Patent Classification⁷: C23F 13/00, 28F 1/30, 1/32, 19/06
- (21) International Application Number: PCT/JP2003/013748
- (22) International Filing Date: 28 October 2003 (28.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2002-315133 30 October 2002 (30.10.2002) JP
60/428,923 26 November 2002 (26.11.2002) US
- (71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SUDO, Takashi [JP/JP]; c/o SHOWA DENKO K.K., OYAMA REGIONAL OFFICE, 480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-8678 (JP).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: HEAT EXCHANGER, HEAT EXCHANGER TUBE MEMBER, HEAT EXCHANGER FIN MEMBER AND PROCESS FOR FABRICATING THE HEAT EXCHANGER



(57) Abstract: Suppose each of the refrigerant tubes 53 of a heat exchanger has a potential A at a surface layer portion 53a of an outer periphery thereof and a potential B at a core 53b of the tube 53 other than the surface layer portion 53a thereof, each of the fins 54 has a potential C, and a fillet 59 formed at the brazed portion between the tube 53 and the fin 54 has a potential D. These potentials then have the relationship of $A \neq C \neq D < B$. The potential A of the surface layer portion 53a of the outer periphery of the refrigerant tube 53 is -850 to -800 mV, the potential B of the core 53b of the tube 53 is -710 to -670 mV, the potential C of the fin 54 is -850 to -800 mV, and the potential D of the fillet 59 is -850 to -800 mV.

WO 2004/040038 A1